



◆ Indicates most accurate load

**.25-06 Remington**

**Bullet Weight:** 90 gr                      **Case Trim Length:** 2.484"                      **S.D.**     0.195  
**Bullet Style:** Banded Solid Spitzer                      **Primer:** Fed GM210M                      **B.C.**     0.325  
**COAL:** 3.155"                      **Barrel Length:** 24.00"  
**Case:** W-W                      **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 22	53.5	3261	58.5	3536	94
◆ Magnum	59.0	3297	64.0	3519	95

**Bullet Weight:** 100 gr                      **Case Trim Length:** 2.484"                      **S.D.**     0.216  
**Bullet Style:** TSX BT                      **Primer:** Fed GM210M                      **B.C.**     0.370  
**COAL:** 3.080"                      **Barrel Length:** 24"  
**Case:** W-W                      **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ MagPro	55.5	3090	60.5	3323	90
RL 22	50.5	3101	55.5	3320	91

**Bullet Weight:** 115 gr                      **Case Trim Length:** 2.484"                      **S.D.**     0.249  
**Bullet Style:** TSX FB                      **Primer:** Fed GM210M                      **B.C.**     0.335  
**COAL:** 3.090"                      **Barrel Length:** 24"  
**Case:** W-W                      **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4831SC	47.0	2797	52.0	2996	88
Magnum	55.0	2969	60.0	3161	93