



*A 1:9.5" or faster twist is recommended for the 150-grain TSX.

◆ Indicates most accurate load

.270 Winchester

Bullet Weight: 110 gr	Case Trim Length: 2.530"	S.D.	0.205
Bullet Style: TSX BT	Primer: Fed GM210M	B.C.	0.323
COAL: 3.240"	Barrel Length: 24"		
Case: R-P	Twist Rate: 1:10"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4350	56.0	3231	59.0	3430	97
Hunter	59.0	3321	63.5	3524	99

Bullet Weight: 120 gr	Case Trim Length: 2.530"	S.D.	0.223
Bullet Style: Banded Solid Spitzer	Primer: Fed GM210M	B.C.	0.438
COAL: 3.280"	Barrel Length: 24"		
Case: R-P	Twist Rate: 1:10"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ IMR 4350	56.0	3183	60.0	3379	105
Hunter	57.0	3213	63.0	3401	101

Bullet Weight: 130 gr	Case Trim Length: 2.530"	S.D.	0.242
Bullet Style: TSX BT	Primer: Fed GM210M	B.C.	0.431
COAL: 3.300"	Barrel Length: 24"		
Case: R-P	Twist Rate: 1:10"		

Bullet Weight: 130 gr	Case Trim Length: 2.530"	S.D.	0.242
Bullet Style: MRX BT	Primer: Fed GM210M	B.C.	0.380
COAL: 3.225"	Barrel Length: 24"		
Case: R-P	Twist Rate: 1:10"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4350	52.0	2927	55.0	3133	93
RL 19	56.0	3026	59.5	3211	102

.270 Winchester

Bullet Weight: 140 gr **Case Trim Length:** 2.530" **S.D.** 0.261
Bullet Style: TSX BT **Primer:** Fed GM210M **B.C.** 0.404
COAL: 3.210" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4350	51.0	2852	54.0	3030	95
Hunter	53.0	2855	56.0	3045	93

Bullet Weight: 150 gr **Case Trim Length:** 2.530" **S.D.** 0.279
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.386
COAL: 3.210" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Bullet Weight: 150 gr **Case Trim Length:** 2.530" **S.D.** 0.279
Bullet Style: MRX BT **Primer:** Fed GM210M **B.C.** 0.425
COAL: 3.225" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4350	49.5	2717	53.0	2897	99
RL 19	51.0	2721	55.0	2909	100
