



\*A twist rate of 1:9" or faster is recommended for the 175-grain TSX.

◆ Indicates most accurate load

**.280 Remington**

**Bullet Weight:** 120 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.213  
**Bullet Style:** TSX BT    **Primer:** Fed GM210M                      **B.C.**     0.349  
**COAL:** 3.235"    **Barrel Length:** 24"  
**Case:** Winchester    **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 19	56.0	3002	59.5	3175	97
◆ MagPro	63.0	3051	68.5	3246	101

**Bullet Weight:** 140 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.248  
**Bullet Style:** TSX BT    **Primer:** Fed GM210M                      **B.C.**     0.394  
**COAL:** 3.235"    **Barrel Length:** 24"  
**Case:** Winchester    **Twist Rate:** 1:10"

**Bullet Weight:** 140 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.248  
**Bullet Style:** Banded Solid SPIT    **Primer:** Fed GM210M                      **B.C.**     0.464  
**COAL:** 3.275"    **Barrel Length:** 24"  
**Case:** Winchester    **Twist Rate:** 1:10"

**Bullet Weight:** 140 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.248  
**Bullet Style:** MRX BT    **Primer:** Fed GM210M                      **B.C.**     0.406  
**COAL:** 3.270"    **Barrel Length:** 24"  
**Case:** Winchester    **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ XMR 3100	53.0	2752	56.5	2950	99
MagPro	59.0	2818	63.5	2998	97

**Bullet Weight:** 150 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.266  
**Bullet Style:** TSX BT    **Primer:** Fed GM210M                      **B.C.**     0.408  
**COAL:** 3.250"    **Barrel Length:** 24"  
**Case:** Winchester    **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ XMR 3100	49.0	2625	53.0	2809	95
RL 22	50.0	2656	54.0	2863	92

## .280 Remington

**Bullet Weight:** 160 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.283  
**Bullet Style:** TSX FB                                      **Primer:** Fed GM210M                      **B.C.**     0.392  
**COAL:** 3.250"                                      **Barrel Length:** 24"  
**Case:** Winchester                                      **Twist Rate:** 1:10"

**Bullet Weight:** 160 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.283  
**Bullet Style:** MRX BT                                      **Primer:** Fed GM210M                      **B.C.**     0.439  
**COAL:** 3.270"                                      **Barrel Length:** 24"  
**Case:** Winchester                                      **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ IMR 4831	46.0	2474	50.0	2673	91
MagPro	53.5	2552	58.5	2744	93

---

**Bullet Weight:** 175 gr                      **Case Trim Length:** 2.530"                      **S.D.**     0.310  
**Bullet Style:** TSX FB                                      **Primer:** Fed GM210M                      **B.C.**     0.417  
**COAL:** 3.250"                                      **Barrel Length:** 24"  
**Case:** Winchester                                      **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
XMR 3100	47.5	2406	51.0	2636	96
♦ RL 22	46.5	2376	52.0	2564	94

---