



*Recommend crimping case mouth into front cannelure groove.

◆ Indicates most accurate load

.375 Remington Ultra Magnum

Bullet Weight: 235 gr **Case Trim Length:** 2.840" **S.D.** 0.239
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.270
COAL: 3.575 **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:12"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Hunter	97.0	3040	105.0	3237	98
◆ RL 19	100.0	2996	107.0	3191	106

Bullet Weight: 270 gr **Case Trim Length:** 2.840" **S.D.** 0.274
Bullet Style: Banded Solid **Primer:** Fed GM215M **B.C.** 0.284
COAL: 3.550" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:12"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
AA 2700	87.0	2750	94.0	2977	87
◆ RL 19	99.0	2888	106.0	3078	106

Bullet Weight: 270 gr **Case Trim Length:** 2.840" **S.D.** 0.274
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.326
COAL: 3.575 **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:12"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4350	88.0	2767	96.0	2959	98
Hunter	90.5	2765	98.5	2983	95

.375 RUM

Bullet Weight: 300 gr **Case Trim Length:** 2.840" **S.D.** 0.305
Bullet Style: Banded Solid **Primer:** Fed GM215M **B.C.** 0.307
COAL: 3.575 **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:12"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4350	88.0	2688	95.0	2863	97
◆ H4831SC	96.0	2696	103.0	2871	105

Bullet Weight: 300 gr **Case Trim Length:** 2.840" **S.D.** 0.305
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.357
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:12"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Hunter	87.0	2605	94.0	2790	94
◆ IMR 4831	89.0	2597	97.0	2823	107
