



*Recommend crimping case mouth into front cannelure.

*Barnes 450- and 500-grain TSX bullets have the front cannelure positioned to maximize case capacity in the .458 Win Mag. When loading these bullets in the .458 Lott we recommend trimming the cases back to 2.760", so that these bullets can be loaded within the SAAMI spec COAL of 3.600". If your magazine box will handle cartridges longer than 3.600", this step is not necessary.

◆ Indicates most accurate load

.458 Lott

Bullet Weight: 450 gr **Case Trim Length:** 2.760" **S.D.** 0.306
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.369
COAL: 3.600" **Barrel Length:** 24"
Case: Hornady **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ BL-C(2)	78.0	1952	86.0	2322	105
Tac	73.5	2149	81.5	2366	101

Bullet Weight: 450 gr **Case Trim Length:** 2.760" **S.D.** 0.306
Bullet Style: Banded Solid **Primer:** Fed GM215M **B.C.** 0.362
COAL: 3.580" **Barrel Length:** 24"
Case: Hornady **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H335	78.0	2252	86.0	2456	97
◆ IMR 4895	75.0	2170	81.0	2365	105

Bullet Weight: 500 gr **Case Trim Length:** 2.760" **S.D.** 0.341
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.412
COAL: 3.600" **Barrel Length:** 24"
Case: Hornady **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H335	69.0	1983	75.5	2167	99
◆ TAC	68.5	2000	76.5	2183	103

Bullet Weight: 500 gr **Case Trim Length:** 2.760" **S.D.** 0.341
Bullet Style: Banded Solid **Primer:** Fed GM215M **B.C.** 0.394
COAL: 3.580" **Barrel Length:** 24"
Case: Hornady **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
BL-C(2)	77.5	2001	85.5	2264	105
◆ H4895	69.0	2050	75.0	2217	105