



*A slight crimp was used to ensure the bullet neck tension was strong enough to keep the bullet from moving.

◆ Indicates most accurate load

.458 Winchester Magnum

Bullet Weight: 450 gr **Case Trim Length:** 2.490" **S.D.** 0.306
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.369
COAL: 3.340" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H335	68.5	2076	72.5	2232	101
◆ TAC	68.5	2109	73.5	2242	105

Bullet Weight: 450 gr **Case Trim Length:** 2.490" **S.D.** 0.306
Bullet Style: Banded Solid **Primer:** Fed GM215M **B.C.** 0.362
COAL: 3.310" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ X-Terminator	68.0	2173	74.0	2328	101
H335	73.0	2229	79.0	2385	102

Bullet Weight: 500 gr **Case Trim Length:** 2.490" **S.D.** 0.341
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.412
COAL: 3.340" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ XMR 2015	54.5	1804	58.5	1930	101
TAC	62.5	1915	67.0	2040	105

Bullet Weight: 500 gr **Case Trim Length:** 2.490" **S.D.** 0.341
Bullet Style: Banded Solid **Primer:** Fed GM215M **B.C.** 0.394
COAL: 3.310" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4198	49.0	1857	55.5	1999	93
TAC	67.0	2062	72.5	2194	105