



*A 1:9" or faster twist is recommended for the 175-grain TSX bullet.

◆ Indicates most accurate load

7mm Remington Ultra Magnum

Bullet Weight: 110 gr **Case Trim Length:** 2.840" **S.D.** 0.195
Bullet Style: TTSX FB **Primer:** Fed 215 **B.C.** 0.319
COAL: 3.600" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 22	89.5	3519	95.5	3761	90
◆ 8700	108.5	3537	114.5	3644	99

Bullet Weight: 120 gr **Case Trim Length:** 2.840" **S.D.** 0.213
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.349
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 22	88.0	3397	94.0	3673	91
◆ IMR 7828SSC	89.5	3362	93.5	3612	87

Bullet Weight: 140 gr **Case Trim Length:** 2.840" **S.D.** 0.248
Bullet Style: Banded Spitzer Solid **Primer:** Fed GM215M **B.C.** 0.464
COAL: 3.590" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Bullet Weight: 140 gr **Case Trim Length:** 2.840" **S.D.** 0.248
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.394
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Bullet Weight: 140 gr **Case Trim Length:** 2.840" **S.D.** 0.248
Bullet Style: MRX BT **Primer:** Fed GM215M **B.C.** 0.406
COAL: 3.580" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4831SC	83.5	3136	89.0	3335	88
RL 25	87.5	3175	93.5	3427	92

7mm Remington Ultra Magnum

Bullet Weight: 150 gr **Case Trim Length:** 2.840" **S.D.** 0.266
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.408
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ IMR 7828SSC	81.0	2999	88.0	3249	85
RL 25	83.0	3054	91.0	3306	90

Bullet Weight: 160 gr **Case Trim Length:** 2.840" **S.D.** 0.283
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.392
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Bullet Weight: 160 gr **Case Trim Length:** 2.840" **S.D.** 0.283
Bullet Style: MRX BT **Primer:** Fed GM215M **B.C.** 0.439
COAL: 3.580" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ IMR 7828SSC	77.0	2858	83.5	3070	82
US869	96.5	3015	102.5	3211	93

Bullet Weight: 175 gr **Case Trim Length:** 2.840" **S.D.** 0.310
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.417
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
AA 8700	93.5	2851	99.0	3072	93
♦ H50BMG	87.5	2832	95.5	3024	99