



\*A 1:9.5" or faster twist is recommended for the 150-grain TSX.

◆ Indicates most accurate load

**.270 Winchester**

**Bullet Weight:** 85 gr                      **Case Trim Length:** 2.530"                      **S.D.**      0.158  
**Bullet Style:** MPG FB                      **Primer:** Fed 210                      **B.C.**      0.229  
**COAL:** 3.100"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:10"

| Powder     | Minimum         |                | Maximum         |                |                  |
|------------|-----------------|----------------|-----------------|----------------|------------------|
|            | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ IMR 4320 | 51.5            | 3497           | 56.5            | 3770           | 93               |
| 2700       | 61.0            | 3654           | 66.0            | 3867           | 101              |

**Bullet Weight:** 85 gr                      **Case Trim Length:** 2.530"                      **S.D.**      0.158  
**Bullet Style:** TSX FB                      **Primer:** Fed 210                      **B.C.**      0.246  
**COAL:** 3.080"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:10"

| Powder  | Minimum         |                | Maximum         |                |                  |
|---------|-----------------|----------------|-----------------|----------------|------------------|
|         | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ RL 17 | 59.0            | 3609           | 64.0            | 3912           | 105              |
| 2700    | 62.5            | 3719           | 67.5            | 3935           | 103              |

**Bullet Weight:** 95 gr                      **Case Trim Length:** 2.530"                      **S.D.**      0.177  
**Bullet Style:** TTSX BT                      **Primer:** Fed 210                      **B.C.**      0.296  
**COAL:** 3.100"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:10"

| Powder  | Minimum         |                | Maximum         |                |                  |
|---------|-----------------|----------------|-----------------|----------------|------------------|
|         | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ RL 17 | 56.0            | 3402           | 61.0            | 3709           | 102              |
| 2700    | 59.5            | 3544           | 64.5            | 3729           | 100              |

**.270 Winchester**

**Bullet Weight:** 110 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.205  
**Bullet Style:** TSX BT                                      **Primer:** Fed GM210M                      **B.C.** 0.323  
**COAL:** 3.240"                                      **Barrel Length:** 24"  
**Case:** R-P    **Twist Rate:** 1:10"

| Powder  | Minimum         |                | Maximum         |                |                  |
|---------|-----------------|----------------|-----------------|----------------|------------------|
|         | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ H4350 | 56.0            | 3231           | 59.0            | 3430           | 97               |
| Hunter  | 59.0            | 3321           | 63.5            | 3524           | 99               |

**Bullet Weight:** 120 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.223  
**Bullet Style:** Banded Solid Spitzer                                      **Primer:** Fed GM210M                      **B.C.** 0.438  
**COAL:** 3.280"                                      **Barrel Length:** 24"  
**Case:** R-P    **Twist Rate:** 1:10"

| Powder     | Minimum         |                | Maximum         |                |                  |
|------------|-----------------|----------------|-----------------|----------------|------------------|
|            | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ IMR 4350 | 56.0            | 3183           | 60.0            | 3379           | 105              |
| Hunter     | 57.0            | 3213           | 63.0            | 3401           | 101              |

**Bullet Weight:** 130 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.242  
**Bullet Style:** TSX BT                                      **Primer:** Fed GM210M                      **B.C.** 0.431  
**COAL:** 3.300"                                      **Barrel Length:** 24"  
**Case:** R-P    **Twist Rate:** 1:10"

**Bullet Weight:** 130 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.242  
**Bullet Style:** MRX BT                                      **Primer:** Fed GM210M                      **B.C.** 0.380  
**COAL:** 3.225"                                      **Barrel Length:** 24"  
**Case:** R-P    **Twist Rate:** 1:10"

| Powder  | Minimum         |                | Maximum         |                |                  |
|---------|-----------------|----------------|-----------------|----------------|------------------|
|         | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ H4350 | 52.0            | 2927           | 55.0            | 3133           | 93               |
| RL 19   | 56.0            | 3026           | 59.5            | 3211           | 102              |

**.270 Winchester**

**Bullet Weight:** 140 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.261  
**Bullet Style:** TSX BT                      **Primer:** Fed GM210M                      **B.C.** 0.404  
**COAL:** 3.210"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:10"

| Powder | Minimum         |                | Maximum         |                |                  |
|--------|-----------------|----------------|-----------------|----------------|------------------|
|        | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| H4350  | 51.0            | 2852           | 54.0            | 3030           | 95               |
| Hunter | 53.0            | 2855           | 56.0            | 3045           | 93               |

---

**Bullet Weight:** 150 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.279  
**Bullet Style:** TSX FB                      **Primer:** Fed GM210M                      **B.C.** 0.386  
**COAL:** 3.210"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:10"

**Bullet Weight:** 150 gr                      **Case Trim Length:** 2.530"                      **S.D.** 0.279  
**Bullet Style:** MRX BT                      **Primer:** Fed GM210M                      **B.C.** 0.425  
**COAL:** 3.225"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:10"

| Powder   | Minimum         |                | Maximum         |                |                  |
|----------|-----------------|----------------|-----------------|----------------|------------------|
|          | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| IMR 4350 | 49.5            | 2717           | 53.0            | 2897           | 99               |
| RL 19    | 51.0            | 2721           | 55.0            | 2909           | 100              |

---