



*A 1:12" or faster twist is recommended for 45-grain Banded Spitzer and 53-grain TSX bullets.

*A 1:10" or faster twist is recommended for 50-grain Varmint Grenade bullets.

*We did not shoot data for the 62- and 70-grain TSX bullets because they won't stabilize in rifling with a 1:12" twist. The ogives of these two bullets don't meet SAAMI specs unless the case mouth is positioned over the ogive.

◆ Indicates most accurate load

.22-250 Remington

Bullet Weight: 36 gr **Case Trim Length:** 1.902" **S.D.** 0.102
Bullet Style: Varmint Grenade **Primer:** Fed GM210M **B.C.** 0.149
COAL: 2.350" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ BL-C(2)	37.0	3961	40.5	4348	88
RL 15	36.0	4002	40.0	4417	98

Bullet Weight: 45 gr **Case Trim Length:** 1.902" **S.D.** 0.128
Bullet Style: Banded Spitzer Solid **Primer:** Fed GM210M **B.C.** 0.195
COAL: 2.350" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:14"

Bullet Weight: 45 gr **Case Trim Length:** 1.902" **S.D.** 0.128
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.188
COAL: 2.350" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
TAC	34.0	3664	37.5	4015	83
◆ AA 2520	37.5	3727	41.0	4060	91

.22-250 Remington

Bullet Weight: 50 gr
Bullet Style: TSX FB
COAL: 2.350"
Case: Winchester

Case Trim Length: 1.902"
Primer: Fed 210
Barrel Length: 24"
Twist Rate: 1:14"

S.D. 0.142
B.C. 0.197

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H380	37.5	3628	40.5	3853	94
H414	38.0	3621	41.0	3873	92

Bullet Weight: 50 gr
Bullet Style: Varmint Grenade
COAL: 2.350"
Case: Winchester

Case Trim Length: 1.902"
Primer: Fed GM210M
Barrel Length: 25"
Twist Rate: 1:14"

S.D. 0.142
B.C. 0.183

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR4895	32.0	3662	35.0	3873	90
H414	38.0	3619	41.0	3903	96

Bullet Weight: 53 gr
Bullet Style: TSX FB
COAL: 2.350"
Case: Winchester

Case Trim Length: 1.902"
Primer: Fed GM210M
Barrel Length: 24"
Twist Rate: 1:14"

S.D. 0.151
B.C. 0.204

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
TAC	32.0	3409	36.0	3764	81
RL 15	34.5	3452	38.0	3848	96
