



*A 1:12" or faster twist rate is required to stabilize 53-grain TSX and 45-grain Banded Spitzer bullets.

♦ Indicates most accurate load

.220 Swift

Bullet Weight: 36 gr **Case Trim Length:** 2.195" **S.D.** 0.102
Bullet Style: Varmint Grenade **Primer:** Fed GM210M **B.C.** 0.149
COAL: 2.635" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Varget	39.0	4137	42.0	4391	95
♦ AA 2700	44.0	4164	47.0	4414	98

Bullet Weight: 45 gr **Case Trim Length:** 2.195" **S.D.** 0.128
Bullet Style: Banded Spitzer Solid **Primer:** Fed GM210M **B.C.** 0.195
COAL: 2.650" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Bullet Weight: 45 gr **Case Trim Length:** 2.195" **S.D.** 0.128
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.188
COAL: 2.650" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 15	37.5	3824	40.5	4105	92
♦ H380	42.5	3931	45.5	4125	97

Bullet Weight: 50 gr **Case Trim Length:** 2.195" **S.D.** 0.142
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.197
COAL: 2.650" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ H380	40.5	3698	43.5	3929	93
AA 2700	40.5	3722	43.5	3944	91

Bullet Weight: 53 gr **Case Trim Length:** 2.195" **S.D.** 0.151
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.204
COAL: 2.650" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H380	39.5	3553	43.5	3860	95
♦ IMR 4007SSC	39.5	3584	42.5	3812	99