



*Load data for this cartridge was tested at the standard SAAMI pressure level—not the higher +P pressure levels listed in some manuals.

◆ Indicates most accurate load

.257 Roberts

Bullet Weight: 80 gr **Case Trim Length:** 2.223" **S.D.** 0.173
Bullet Style: TTSX BT **Primer:** Fed 210 **B.C.** 0.316
COAL: 2.830" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ IMR 4350	43.0	2907	47.0	3287	97
Hunter	46.0	3148	50.0	3447	93

Bullet Weight: 90 gr **Case Trim Length:** 2.223" **S.D.** 0.195
Bullet Style: Banded Solid Spitzer **Primer:** Fed GM210M **B.C.** 0.325
COAL: 2.780" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
AA 2700	42.5	3070	46.5	3333	88
◆ RL 19	45.0	3008	49.0	3275	101

Bullet Weight: 100 gr **Case Trim Length:** 2.223" **S.D.** 0.216
Bullet Style: TSX BT **Primer:** Fed GM210M **B.C.** 0.336
COAL: 2.780" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4350	40.5	2883	44.5	3124	96
◆ Hunter	42.5	2926	46.5	3126	91

Bullet Weight: 115 gr **Case Trim Length:** 2.223" **S.D.** 0.249
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.335
COAL: 2.780" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4350	35.0	2546	39.0	2769	89
XMR 3100	41.5	2686	45.5	2907	102