



◆ Indicates most accurate loads

.260 Remington

Bullet Weight: 110 gr **Case Trim Length:** 2.025" **S.D.** 0.225
Bullet Style: Banded Solid Spitzer **Primer:** Fed GM210M **B.C.** 0.452
COAL: 2.750" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9"

| Powder | Minimum | | Maximum | | |
|----------|-----------------|----------------|-----------------|----------------|------------------|
| | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| IMR 4350 | 43.0 | 2877 | 47.0 | 3099 | 105 |
| ◆ H4350 | 41.5 | 2830 | 45.5 | 3058 | 98 |

Bullet Weight: 120 gr **Case Trim Length:** 2.025" **S.D.** 0.246
Bullet Style: TSX BT **Primer:** Fed GM210M **B.C.** 0.381
COAL: 2.705" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9"

| Powder | Minimum | | Maximum | | |
|------------|-----------------|----------------|-----------------|----------------|------------------|
| | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ IMR 4350 | 40.0 | 2707 | 44.5 | 2939 | 100 |
| RL 19 | 41.5 | 2728 | 45.5 | 2915 | 100 |

Bullet Weight: 130 gr **Case Trim Length:** 2.025" **S.D.** 0.266
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.365
COAL: 2.705" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9"

| Powder | Minimum | | Maximum | | |
|----------|-----------------|----------------|-----------------|----------------|------------------|
| | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ◆ RL 19 | 41.0 | 2598 | 45.0 | 2758 | 101 |
| XMR 3100 | 41.0 | 2591 | 45.0 | 2809 | 105 |