



\*This load data was test fired up to the SAAMI maximum average pressure (MAP) of 51,000 psi.

◆ Indicates most accurate loads

### 6.5 x 55 Swedish Mauser

**Bullet Weight:** 110 gr                      **Case Trim Length:** 2.155"                      **S.D.**     0.225  
**Bullet Style:** Banded Spitzer Solid                      **Primer:** Fed GM210M                      **B.C.**     0.452  
**COAL:** 2.980"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:8"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Mag Pro	49.0	2768	54.5	3007	100
◆ RL 22	45.5	2737	49.0	2931	98

**Bullet Weight:** 120 gr                      **Case Trim Length:** 2.155"                      **S.D.**     0.246  
**Bullet Style:** TSX BT                      **Primer:** Fed GM210M                      **B.C.**     0.381  
**COAL:** 2.950"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:8"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Mag Pro	46.0	2568	51.0	2814	93
◆ RL 22	41.0	2530	46.0	2762	92

**Bullet Weight:** 130 gr                      **Case Trim Length:** 2.155"                      **S.D.**     0.266  
**Bullet Style:** TSX FB                      **Primer:** Fed GM210M                      **B.C.**     0.365  
**COAL:** 2.950"                      **Barrel Length:** 24"  
**Case:** R-P                      **Twist Rate:** 1:8"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Mag Pro	44.0	2443	49.0	2655	92
◆ RL 22	39.0	2399	44.0	2594	91