



*A twist rate of 1:9" or faster is recommended for the 175-grain TSX.

◆ Indicates most accurate load

.280 Remington

Bullet Weight: 120 gr	Case Trim Length: 2.530"	S.D.	0.213
Bullet Style: TSX BT	Primer: Fed GM210M	B.C.	0.349
COAL: 3.235"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H414	49.5	2920	53.5	3123	80
IMR 4350	53.0	2973	55.5	3123	93
H4350	51.0	2973	54.0	3142	87
Hunter	54.5	2998	58.0	3174	89
RL 19	56.0	3002	59.5	3175	97
VIT N560	57.0	2980	60.5	3166	---
IMR 4831	54.5	2982	57.5	3135	97
XMR 3100	56.0	2987	59.5	3178	101
H4831SC	53.5	2922	58.0	3129	94
◆ MagPro	63.0	3051	68.5	3246	101

Bullet Weight: 140 gr	Case Trim Length: 2.530"	S.D.	0.248
Bullet Style: TSX BT	Primer: Fed GM210M	B.C.	0.394
COAL: 3.235"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		

Bullet Weight: 140 gr	Case Trim Length: 2.530"	S.D.	0.248
Bullet Style: Banded Solid SPIT	Primer: Fed GM210M	B.C.	0.464
COAL: 3.275"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		

Bullet Weight: 140 gr	Case Trim Length: 2.530"	S.D.	0.248
Bullet Style: MRX BT	Primer: Fed GM210M	B.C.	0.406
COAL: 3.270"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4350	49.5	2730	52.5	2876	91
H4350	47.0	2702	52.0	2919	87
Hunter	51.5	2751	56.5	2984	89
RL 19	51.5	2729	55.5	2924	94
VIT N560	53.0	2734	57.0	2952	---
IMR 4831	51.0	2744	54.5	2938	95
◆ XMR 3100	53.0	2752	56.5	2950	99
H4831SC	51.0	2735	55.0	2908	92
MagPro	59.0	2818	63.5	2998	97
RL 22	53.5	2772	57.0	2970	96

.280 Remington

Bullet Weight: 150 gr
Bullet Style: TSX BT
COAL: 3.250"
Case: Winchester

Case Trim Length: 2.530"
Primer: Fed GM210M
Barrel Length: 24"
Twist Rate: 1:10"

S.D. 0.266
B.C. 0.408

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4350	46.0	2600	50.0	2793	89
H4350	43.5	2572	48.0	2766	82
RL 19	49.0	2648	53.5	2864	92
VIT N560	50.0	2618	53.5	2791	---
IMR 4831	48.0	2607	52.0	2813	92
◆ XMR 3100	49.0	2625	53.0	2809	95
H4831SC	47.0	2582	51.5	2769	88
MagPro	56.0	2710	60.0	2879	93
RL 22	50.0	2656	54.0	2863	92
IMR 7828SSC	50.0	2584	54.5	2805	90

Bullet Weight: 160 gr
Bullet Style: TSX FB
COAL: 3.250"
Case: Winchester

Case Trim Length: 2.530"
Primer: Fed GM210M
Barrel Length: 24"
Twist Rate: 1:10"

S.D. 0.283
B.C. 0.392

Bullet Weight: 160 gr
Bullet Style: MRX BT
COAL: 3.270"
Case: Winchester

Case Trim Length: 2.530"
Primer: Fed GM210M
Barrel Length: 24"
Twist Rate: 1:10"

S.D. 0.283
B.C. 0.439

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4350	42.0	2426	47.0	2658	82
RL 19	47.0	2522	51.0	2704	90
VIT N560	48.5	2506	51.5	2662	---
◆ IMR 4831	46.0	2474	50.0	2673	91
XMR 3100	48.0	2517	51.5	2677	94
H4831SC	44.5	2420	49.5	2627	86
MagPro	53.5	2552	58.5	2744	93
RL 22	48.5	2496	53.0	2722	92
IMR 7828SSC	48.5	2460	52.5	2637	89
H1000	51.5	2482	57.0	2676	99

.280 Remington

Bullet Weight: 175 gr

Bullet Style: TSX FB

COAL: 3.250"

Case: Winchester

Case Trim Length: 2.530"

Primer: Fed GM210M

Barrel Length: 24"

Twist Rate: 1:10"

S.D. 0.310

B.C. 0.417

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 19	45.0	2376	48.5	2532	88
VIT N560	46.0	2347	49.0	2526	---
IMR 4831	45.0	2380	49.5	2558	93
XMR 3100	47.5	2406	51.0	2636	96
H4831SC	44.5	2312	48.0	2497	87
MagPro	50.0	2415	56.0	2608	92
◆ RL 22	46.5	2376	52.0	2564	94
IMR 7828SSC	48.0	2353	52.0	2528	91
H1000	52.0	2407	56.0	2558	101
Magnum	52.0	2357	56.0	2510	93
