



*With 130- and 168-grain TSX bullets, the case mouth falls in front of the ogive/shank junction at the listed COAL. Use a factory crimp die to lightly crimp the case mouth against these bullets to increase neck tension and improve feeding.

*Powder charges of less than 100 percent density are recommended when loading 165-grain Banded Spitzers, because of the length of the bullets.

◆ Indicates most accurate load

.300 H&H Magnum

Bullet Weight: 130 gr **Case Trim Length:** 2.840" **S.D.** 0.196
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.340
COAL: 3.515" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ IMR 4895	63.0	3272	66.0	3431	87
VIT N550	66.0	3298	71.0	3510	88

Bullet Weight: 150 gr **Case Trim Length:** 2.840" **S.D.** 0.226
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.369
COAL: 3.515" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Bullet Weight: 150 gr **Case Trim Length:** 2.840" **S.D.** 0.226
Bullet Style: MRX BT **Primer:** Fed GM215M **B.C.** 0.420
COAL: 3.550" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H414	63.5	3036	67.0	3196	83
IMR 4350	67.0	3085	70.5	3244	97

.300 H&H Magnum

Bullet Weight: 165 gr	Case Trim Length: 2.840"	S.D.	0.248
Bullet Style: TSX BT	Primer: Fed GM215M	B.C.	0.380
COAL: 3.515"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		
Bullet Weight: 165 gr	Case Trim Length: 2.840"	S.D.	0.248
Bullet Style: MRX BT	Primer: Fed GM215M	B.C.	0.439
COAL: 2.820"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		
Bullet Weight: 165 gr	Case Trim Length: 2.840"	S.D.	0.248
Bullet Style: Banded Solid Spitzer	Primer: Fed GM215M	B.C.	0.438
COAL: 3.540"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		
Bullet Weight: 168 gr	Case Trim Length: 2.840"	S.D.	0.253
Bullet Style: TSX BT	Primer: Fed GM215M	B.C.	0.404
COAL: 3.515"	Barrel Length: 24"		
Case: Winchester	Twist Rate: 1:10"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 19	67.0	2905	71.5	3118	97
◆ H4831SC	68.0	2888	72.5	3053	98

.300 H&H Magnum

Bullet Weight: 180 gr **Case Trim Length:** 2.840" **S.D.** 0.271
Bullet Style: MRX BT **Primer:** Fed GM215M **B.C.** 0.473
COAL: 3.515" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Bullet Weight: 180 gr **Case Trim Length:** 2.840" **S.D.** 0.271
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.453
COAL: 3.515" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ XMR 3100	66.0	2811	70.0	2966	101
RL 22	67.0	2829	71.0	3009	98

Bullet Weight: 200 gr **Case Trim Length:** 2.840" **S.D.** 0.301
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.423
COAL: 3.515" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ H414	55.0	2486	60.0	2652	79
MagPro	68.0	2626	71.0	2826	92

Bullet Weight: 220 gr **Case Trim Length:** 2.840" **S.D.** 0.331
Bullet Style: SRN FB **Primer:** Fed GM215M **B.C.** 0.305
COAL: 3.525" **Barrel Length:** 24"
Case: Winchester **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ Hunter	59.5	2516	62.0	2650	83
RL 22	64.0	2569	67.5	2717	96