



## 6.5 PRC Load Data

**Case:** Atlas

**Barrel Length:** 24"

**Case Trim Length:** 2.020"

**Primer:** Rem 9 1/2m

**Twist Rate:** 1:8"

<b>Bullet Weight</b>	<b>Bullet Type</b>	<b>Bullet SKU</b>	<b>Bullet S.D</b>	<b>Bullet G1 B.C</b>	<b>Cartridge O.A.L</b>
120gr	TSX BT	30244	0.246	0.381	2.825"
120gr	TTSX BT	30242	0.246	0.412	2.865"
120gr	Match Burner	30234	0.246	0.460	2.825"

  

<b>Powder</b>	<b>Minimum</b>		<b>Maximum</b>	
	<b>Charge (grains)</b>	<b>Velocity (fps)</b>	<b>Charge (grains)</b>	<b>Velocity (fps)</b>
H4831sc	49.8	2918	54.7	3094
Hybrid 100V	45.6	2894	50.7	3126
IMR 7977	51.6	2912	56.7	3136
RL 23	47.7	2916	53.0	3142
IMR 7828	48.7	2894	54.2	3154
H1000	53.1	2993	58.4c	3176
RL 26	50.4	2998	55.4	3203



## 6.5 PRC Load Data

Case: Atlas

Barrel Length: 24"

Case Trim Length: 2.020"

Primer: Rem 9 1/2m

Twist Rate: 1:8"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
127gr	LRX BT	30228	0.260	0.468	2.865"
130gr	TSX FB	30246	0.266	0.365	2.800"
130gr	TSX BT	31140	0.266	0.411	2.800"

Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
H4831sc	49.2	2801	54.6	3017
Hybrid 100V	45.5	2853	49.5	3037
RL 23	46.8	2812	52.0	3042
IMR 7977	51.1	2762	56.8c	3053
IMR 7828	48.8	2829	54.2	3074
H1000	52.3	2841	58.1c	3085
Power Pro 4000MR	48.1	2818	53.4	3091
RL 17	45.4	2857	49.9	3091
RL 26	49.5	2868	55.0	3107
Magnum	57.7	2897	64.1c	3190



## 6.5 PRC Load Data

Case: Atlas

Barrel Length: 24"

Case Trim Length: 2.020"

Primer: Rem 9 1/2m

Twist Rate: 1:8"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
140gr	Match Burner	30230 31144 <sub>(500pk)</sub>	0.287	0.586	2.940"
145gr	Match Burner	30100 30102 <sub>(500pk)</sub>	0.297	0.703	2.940"
		Minimum	Maximum		
Powder	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	
IMR 7977	51.0	2610	56.7c	2913	
H4831sc	50.4	2680	56.0	2923	
Power Pro 4000MR	46.7	2635	51.9	2923	
RL 23	47.9	2674	53.2	2931	
H1000	52.6	2713	58.5c	2957	
Magpro	53.8	2696	59.7	2966	
Magnum	55.5	2684	61.7c	2978	
RL 26	50.3	2697	55.9	2984	
Retumbo	53.8	2734	59.8c	3012	