



## 270 Winchester Load Data

**Case:** Remington

**Barrel Length:** 24"

**Case Trim Length:** 2.530"

**Primer:** Rem 9 1/2

**Twist Rate:** 1:10"

<b>Bullet Weight</b>	<b>Bullet Type</b>	<b>Bullet SKU</b>	<b>Bullet S.D</b>	<b>Bullet G1 B.C</b>	<b>Cartridge O.A.L</b>
85gr	TSX FB	30254	0.158	0.246	3.080"
85gr	MPG FB	30249	0.158	0.229	3.100"
		<b>Minimum Charge</b>	<b>Velocity</b>	<b>Maximum Charge</b>	<b>Velocity</b>
<b>Powder</b>	<b>(grains)</b>	<b>(fps)</b>	<b>(grains)</b>	<b>(fps)</b>	
IMR 4320	50.0	3333	55.5	3673	
RL 15	50.4	3393	56.0	3718	
Win 760	55.5	3408	61.7c	3721	
A-2700	56.3	3459	62.5c	3755	
Varget	52.2	3457	58.0c	3796	
H380	57.4	3571	63.7c	3799	
Big Game	56.7	3513	63.0c	3801	
PowerPro 2000MR	55.0	3500	61.1	3834	



## 270 Winchester Load Data

**Case:** Remington

**Barrel Length:** 24"

**Case Trim Length:** 2.530"

**Primer:** Rem 9 1/2

**Twist Rate:** 1:10"

<b>Bullet Weight</b>	<b>Bullet Type</b>	<b>Bullet SKU</b>	<b>Bullet S.D</b>	<b>Bullet G1 B.C</b>	<b>Cartridge O.A.L</b>
95gr	TTSX BT	30271	0.177	0.292	3.100"
		<b>Minimum</b>		<b>Maximum</b>	
<b>Powder</b>	<b>Charge (grains)</b>	<b>Velocity (fps)</b>	<b>Charge (grains)</b>	<b>Velocity (fps)</b>	
RL 15	49.3	3259	54.8	3603	
Win 760	54.1	3330	60.1c	3604	
H4350	55.9	3266	62.1c	3611	
A-2700	55.3	3360	61.5c	3650	
Big Game	54.9	3361	61.0c	3656	
H380	55.2	3413	61.3c	3670	
RL 17	54.1	3274	60.1c	3673	



## 270 Winchester Load Data

**Case:** Remington

**Barrel Length:** 24"

**Case Trim Length:** 2.530"

**Primer:** Rem 9 1/2

**Twist Rate:** 1:10"

<b>Bullet Weight</b>	<b>Bullet Type</b>	<b>Bullet SKU</b>	<b>Bullet S.D</b>	<b>Bullet G1 B.C</b>	<b>Cartridge O.A.L</b>
110gr	TSX BT	30260	0.205	0.323	3.240"
110gr	TTSX BT	30274	0.205	0.377	3.250"
		<b>Minimum Charge</b>	<b>Velocity</b>	<b>Maximum Charge</b>	<b>Velocity</b>
<b>Powder</b>	<b>(grains)</b>	<b>(fps)</b>	<b>(grains)</b>	<b>(fps)</b>	
RL 15	47.2	3075	52.5	3342	
Win 760	51.7	3089	57.5	3373	
H4350	53.0	3068	58.9c	3381	
A-2700	52.0	3101	57.8c	3404	
H380	51.7	3138	57.5c	3407	
Hybrid 100V	53.2	3175	59.1c	3448	
RL 17	52.2	3132	58.0c	3474	
Hunter	59.1	3260	65.7c	3507	



## 270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:10"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
129gr	LRX BT	30262	0.240	0.463	3.300"
130gr	TSX BT	30264	0.242	0.374	3.250"
130gr	TTSX BT	30276	0.242	0.392	3.210"
		Minimum Charge	Minimum Velocity	Maximum Charge	Maximum Velocity
Powder		(grains)	(fps)	(grains)	(fps)
Win 760		48.1	2812	53.5	3093
H4350		49.7	2845	55.3	3116
H4831sc		54.5	2847	60.5c	3116
StaBall 6.5		50.5	2865	55.7	3140
Hybrid 100V		49.0	2818	54.4	3151
IMR 4350		50.2	2857	55.7c	3165
IMR 4831		51.3	2861	57.0c	3167
A-4350		51.5	2842	57.2c	3168
PowerPro 4000MR		51.0	2870	55.5	3185
RL 17		48.7	2877	54.1	3187
Superformance		52.5	2850	58.3c	3193
RL 19		53.6	2890	59.5c	3207
Hunter		53.8	2956	59.8c	3211



## 270 Winchester Load Data

**Case:** Remington

**Barrel Length:** 24"

**Case Trim Length:** 2.530"

**Primer:** Rem 9 1/2

**Twist Rate:** 1:10"

	<b>Bullet Weight</b>	<b>Bullet Type</b>	<b>Bullet SKU</b>	<b>Bullet S.D</b>	<b>Bullet G1 B.C</b>	<b>Cartridge O.A.L</b>
	140gr	TSX BT	30266	0.261	0.404	3.210"
		<b>Minimum Charge (grains)</b>	<b>Velocity (fps)</b>	<b>Maximum Charge (grains)</b>	<b>Velocity (fps)</b>	
		<b>Powder</b>				
		H4350	48.9	2704	54.4	2995
		IMR 4831	50.1	2712	55.6c	3009
		H4831sc	54.3	2736	60.3c	3018
		IMR 4350	49.4	2703	54.9	3025
Win	Supreme	780	52.4	2715	58.2c	3026
	Hybrid	100V	48.0	2686	53.3	3027
	A-4350		49.9	2719	55.5c	3032
	RL 17		48.1	2731	53.5	3065
	Hunter		52.5	2823	58.4c	3076
	RL 19		52.3	2757	58.1c	3080
	Superformance		51.5	2762	57.2c	3082



## 270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:8"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
150gr	TSX FB	30269	0.279	0.386	3.210"
155gr	LRX BT	32112	0.289	0.540	3.340"
Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	
IMR 4955	46.5	2454	51.7	2762	
IMR 4831	46.2	2505	51.3	2786	
H4350	43.6	2540	48.4	2796	
Win 760	44.2	2553	49.1	2805	
A-4350	47.5	2569	52.8c	2841	
IMR 4350	46.8	2569	52.0	2843	
H4831sc	51.7	2591	57.4c	2850	
RL 17	44.2	2579	49.1	2862	
Hybrid 100V	47.1	2580	52.3	2864	
StaBall 6.5	47.0	2558	52.3	2874	
Hunter	49.1	2635	54.6c	2884	
RL 23	48.4	2621	53.7	2888	
Superformance	48.8	2603	54.2	2899	
Win Supreme 780	51.8	2600	57.5c	2900	
RL 19	50.3	2618	55.9c	2935	

### Notes

150gr TSX FB requires 1:9.5" twist or faster.

155gr LRX BT requires 1:8" twist or faster.