

Barnes VOR-TX LR Ammunition

6mm Creedmoor 95gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.436			G7 BC: 0.215						G1 BC: 0.436			G7 BC: 0.215					
Range Yards	Velocity	Energy	Drop inches	Zero Adj.		Drift			Range Yards	Velocity	Energy	Drop inches	Zero Adj.		Drift		
	f/s	ft-lb		MOA	MIL	inches	MOA	MIL		f/s	ft-lb		inches	MOA	MIL	inches	MOA
0	3150	2094	----	----	----	----	----	----	0	3150	2094	----	----	----	----	----	----
50	3036	1945	0.4	-0.7	-0.2	0.2	0.3	0.1	50	3052	1965	0.3	-0.6	-0.2	0.1	0.3	0.1
100	2925	1805	1.3	-1.2	-0.4	0.6	0.6	0.2	100	2956	1843	1.2	-1.2	-0.3	0.5	0.5	0.2
150	2817	1674	1.2	-0.8	-0.2	1.4	0.9	0.3	150	2862	1728	1.2	-0.7	-0.2	1.2	0.8	0.2
200	2711	1551	0.0	0.0	0.0	2.6	1.3	0.4	200	2770	1619	0.0	0.0	0.0	2.2	1.1	0.3
250	2608	1435	-2.4	0.9	0.3	4.2	1.6	0.5	250	2680	1515	-2.3	0.9	0.3	3.5	1.4	0.4
300	2507	1326	-6.0	1.9	0.6	6.1	2.0	0.6	300	2592	1417	-5.8	1.8	0.5	5.2	1.7	0.5
350	2408	1224	-11.1	3.0	0.9	8.5	2.3	0.7	350	2505	1324	-10.6	2.9	0.8	7.1	2.0	0.6
400	2312	1128	-17.6	4.2	1.2	11.3	2.7	0.8	400	2421	1236	-16.7	4.0	1.2	9.5	2.3	0.7
450	2218	1038	-25.8	5.5	1.6	14.6	3.1	0.9	450	2338	1153	-24.4	5.2	1.5	12.2	2.6	0.8
500	2126	953	-35.7	6.8	2.0	18.3	3.5	1.0	500	2256	1074	-33.6	6.4	1.9	15.3	2.9	0.9

Barnes VOR-TX LR Ammunition

6.5 Creedmoor 127gr LRX BT																			
Altitude: 0 feet Zero Range: 200 yards Wind Speed: 10 mph									Altitude: 5000 feet Zero Range: 200 yards Wind Speed: 10 mph										
Temp: 59 °F Sight Height: 1.5 in Wind Dir: 03:00 O'clk									Temp: 40 °F Sight Height: 1.5 in Wind Dir: 03:00 O'clk										
G1 BC: 0.468 G7 BC: 0.229									G1 BC: 0.468 G7 BC: 0.229										
Range	Velocity	Energy	Drop	Zero Adj.			Drift			Range	Velocity	Energy	Drop	Zero Adj.			Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL		
0	2850	2291	----	----	----	----	----	----	0	2850	2291	----	----	----	----	----	----		
50	2751	2134	0.7	-1.3	-0.4	-0.2	0.3	0.1	50	2765	2156	0.7	-1.2	-0.4	-0.1	0.3	0.1		
100	2654	1986	1.7	-1.6	-0.5	-0.7	0.6	0.2	100	2681	2027	1.7	-1.6	-0.5	-0.6	0.6	0.2		
150	2559	1847	1.5	-1.0	-0.3	-1.5	1.0	0.3	150	2599	1905	1.5	-0.9	-0.3	-1.3	0.8	0.2		
200	2466	1715	0.0	0.0	0.0	-2.8	1.3	0.4	200	2518	1788	0.0	0.0	0.0	-2.4	1.1	0.3		
250	2375	1591	-3.0	1.1	0.3	-4.4	1.7	0.5	250	2439	1678	-2.9	1.1	0.3	-3.8	1.4	0.4		
300	2285	1473	-7.5	2.4	0.7	-6.5	2.1	0.6	300	2361	1572	-7.2	2.3	0.7	-5.5	1.8	0.5		
350	2198	1363	-13.6	3.7	1.1	-9.0	2.5	0.7	350	2285	1472	-13.0	3.6	1.0	-7.6	2.1	0.6		
400	2113	1259	-21.6	5.2	1.5	-12.0	2.9	0.8	400	2210	1377	-20.6	4.9	1.4	-10.1	2.4	0.7		
450	2029	1161	-31.5	6.7	1.9	-15.5	3.3	1.0	450	2136	1287	-29.9	6.3	1.8	-13.0	2.8	0.8		
500	1948	1070	-43.5	8.3	2.4	-19.5	3.7	1.1	500	2064	1201	-41.1	7.9	2.3	-16.3	3.1	0.9		
550	1868	985	-57.8	10.0	2.9	-24.1	4.2	1.2	550	1993	1120	-54.4	9.4	2.7	-20.1	3.5	1.0		
600	1791	905	-74.6	11.9	3.5	-29.3	4.7	1.4	600	1924	1044	-69.8	11.1	3.2	-24.3	3.9	1.1		

Barnes VOR-TX LR Ammunition

6.5 PRC 127gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.468			G7 BC: 0.229						G1 BC: 0.468			G7 BC: 0.229					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3010	2556	----	----	----	----	----	----	0	3010	2556	----	----	----	----	----	----
50	2907	2384	0.5	-1.0	-0.3	-0.2	0.3	0.1	50	2921	2407	0.5	-1.0	-0.3	-0.1	0.2	0.1
100	2807	2222	1.5	-1.4	-0.4	-0.6	0.6	0.2	100	2834	2266	1.4	-1.4	-0.4	-0.5	0.5	0.2
150	2708	2069	1.3	-0.8	-0.2	-1.4	0.9	0.3	150	2749	2132	1.3	-0.8	-0.2	-1.2	0.8	0.2
200	2612	1925	0.0	0.0	0.0	-2.6	1.2	0.4	200	2666	2005	0.0	0.0	0.0	-2.2	1.1	0.3
250	2518	1788	-2.6	1.0	0.3	-4.1	1.6	0.5	250	2584	1883	-2.5	1.0	0.3	-3.5	1.3	0.4
300	2426	1660	-6.6	2.1	0.6	-6.0	1.9	0.6	300	2504	1768	-6.3	2.0	0.6	-5.1	1.6	0.5
350	2336	1539	-12.0	3.3	1.0	-8.3	2.3	0.7	350	2425	1658	-11.5	3.1	0.9	-7.0	1.9	0.6
400	2247	1424	-19.0	4.5	1.3	-11.1	2.6	0.8	400	2347	1554	-18.2	4.3	1.3	-9.3	2.2	0.6
450	2161	1317	-27.8	5.9	1.7	-14.3	3.0	0.9	450	2271	1455	-26.4	5.6	1.6	-12.0	2.5	0.7
500	2076	1216	-38.4	7.3	2.1	-18.0	3.4	1.0	500	2196	1361	-36.4	7.0	2.0	-15.1	2.9	0.8
550	1993	1121	-51.1	8.9	2.6	-22.2	3.9	1.1	550	2123	1271	-48.1	8.4	2.4	-18.5	3.2	0.9
600	1913	1032	-65.9	10.5	3.1	-27.0	4.3	1.2	600	2051	1187	-61.8	9.8	2.9	-22.4	3.6	1.0
650	1834	949	-83.1	12.2	3.6	-32.3	4.7	1.4	650	1980	1106	-77.6	11.4	3.3	-26.7	3.9	1.1
700	1758	872	-102.9	14.0	4.1	-38.2	5.2	1.5	700	1911	1030	-95.5	13.0	3.8	-31.5	4.3	1.3

Barnes VOR-TX LR Ammunition

270 Win 129gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.463			G7 BC: 0.229						G1 BC: 0.463			G7 BC: 0.229					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3140	2825	----	----	----	----	----	----	0	3140	2825	----	----	----	----	----	----
50	3033	2635	0.4	-0.7	-0.2	0.2	0.3	0.1	50	3047	2661	0.3	-0.6	-0.2	0.1	0.2	0.1
100	2928	2457	1.3	-1.2	-0.4	0.6	0.6	0.2	100	2957	2505	1.2	-1.2	-0.3	0.5	0.5	0.1
150	2826	2288	1.2	-0.8	-0.2	1.4	0.9	0.3	150	2868	2357	1.2	-0.7	-0.2	1.2	0.7	0.2
200	2726	2130	0.0	0.0	0.0	2.5	1.2	0.3	200	2781	2217	0.0	0.0	0.0	2.1	1.0	0.3
250	2629	1980	-2.4	0.9	0.3	3.9	1.5	0.4	250	2696	2083	-2.3	0.9	0.3	3.3	1.3	0.4
300	2533	1839	-6.0	1.9	0.6	5.8	1.8	0.5	300	2613	1956	-5.7	1.8	0.5	4.9	1.6	0.5
350	2440	1706	-10.9	3.0	0.9	8.0	2.2	0.6	350	2531	1835	-10.5	2.9	0.8	6.7	1.8	0.5
400	2348	1580	-17.4	4.1	1.2	10.6	2.5	0.7	400	2451	1721	-16.6	4.0	1.2	8.9	2.1	0.6
450	2259	1462	-25.4	5.4	1.6	13.6	2.9	0.8	450	2372	1612	-24.1	5.1	1.5	11.5	2.4	0.7
500	2171	1351	-35.1	6.7	1.9	17.2	3.3	1.0	500	2294	1508	-33.2	6.3	1.8	14.4	2.7	0.8
550	2085	1246	-46.6	8.1	2.4	21.2	3.7	1.1	550	2218	1410	-43.9	7.6	2.2	17.7	3.1	0.9
600	2002	1148	-60.2	9.6	2.8	25.7	4.1	1.2	600	2144	1317	-56.5	9.0	2.6	21.4	3.4	1.0
650	1920	1056	-75.9	11.1	3.2	30.7	4.5	1.3	650	2070	1228	-70.9	10.4	3.0	25.5	3.7	1.1
700	1840	970	-94.0	12.8	3.7	36.4	5.0	1.4	700	1999	1144	-87.3	11.9	3.5	30.1	4.1	1.2

Barnes VOR-TX LR Ammunition

280 Ack Imp 152gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.467			G7 BC: 0.233						G1 BC: 0.467			G7 BC: 0.233					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3000	3038	----	----	----	----	----	----	0	3000	3038	----	----	----	----	----	----
50	2897	2834	0.5	-1.0	-0.3	0.1	0.2	0.1	50	2911	2861	0.5	-1.0	-0.3	0.1	0.2	0.1
100	2797	2640	1.5	-1.4	-0.4	0.6	0.6	0.2	100	2825	2693	1.4	-1.3	-0.4	0.5	0.5	0.1
150	2698	2458	1.3	-0.8	-0.2	1.3	0.8	0.2	150	2739	2533	1.3	-0.8	-0.2	1.1	0.7	0.2
200	2602	2286	0.0	0.0	0.0	2.3	1.1	0.3	200	2656	2381	0.0	0.0	0.0	2.0	1.0	0.3
250	2508	2124	-2.6	1.0	0.3	3.7	1.4	0.4	250	2574	2237	-2.5	1.0	0.3	3.2	1.2	0.4
300	2416	1970	-6.6	2.1	0.6	5.5	1.8	0.5	300	2494	2099	-6.4	2.0	0.6	4.6	1.5	0.4
350	2326	1826	-12.1	3.3	1.0	7.6	2.1	0.6	350	2415	1969	-11.6	3.2	0.9	6.4	1.7	0.5
400	2237	1690	-19.2	4.6	1.3	10.0	2.4	0.7	400	2337	1844	-18.3	4.4	1.3	8.5	2.0	0.6
450	2151	1562	-28.0	5.9	1.7	13.0	2.8	0.8	450	2261	1726	-26.6	5.6	1.6	10.9	2.3	0.7
500	2066	1441	-38.8	7.4	2.2	16.3	3.1	0.9	500	2186	1614	-36.7	7.0	2.0	13.7	2.6	0.8
550	1984	1329	-51.5	8.9	2.6	20.1	3.5	1.0	550	2113	1507	-48.5	8.4	2.4	16.8	2.9	0.8
600	1903	1223	-66.5	10.6	3.1	24.4	3.9	1.1	600	2041	1407	-62.3	9.9	2.9	20.3	3.2	0.9
650	1825	1124	-83.8	12.3	3.6	29.3	4.3	1.3	650	1971	1311	-78.1	11.5	3.3	24.2	3.6	1.0
700	1749	1032	-103.8	14.2	4.1	34.7	4.7	1.4	700	1902	1221	-96.3	13.1	3.8	28.6	3.9	1.1

Barnes VOR-TX LR Ammunition

7mm Remington Magnum 139gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.434			G7 BC: 0.215						G1 BC: 0.434			G7 BC: 0.215					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3210	3181	----	----	----	----	----	----	0	3210	3181	----	----	----	----	----	----
50	3094	2955	0.3	-0.6	-0.2	-0.2	-0.3	-0.1	50	3110	2986	0.3	-0.6	-0.2	-0.1	-0.2	-0.1
100	2981	2743	1.2	-1.2	-0.3	-0.6	-0.6	-0.2	100	3012	2801	1.2	-1.1	-0.3	-0.5	-0.5	-0.1
150	2871	2544	1.1	-0.7	-0.2	-1.4	-0.9	-0.3	150	2916	2626	1.1	-0.7	-0.2	-1.2	-0.8	-0.2
200	2763	2357	0.0	0.0	0.0	-2.6	-1.2	-0.4	200	2823	2460	0.0	0.0	0.0	-2.2	-1.1	-0.3
250	2658	2182	-2.3	0.9	0.3	-4.1	-1.6	-0.5	250	2731	2303	-2.2	0.8	0.2	-3.5	-1.3	-0.4
300	2556	2017	-5.8	1.8	0.5	-6.0	-1.9	-0.6	300	2642	2155	-5.5	1.8	0.5	-5.1	-1.6	-0.5
350	2456	1862	-10.6	2.9	0.8	-8.3	-2.3	-0.7	350	2554	2014	-10.1	2.8	0.8	-7.0	-1.9	-0.6
400	2358	1716	-16.9	4.0	1.2	-11.0	-2.6	-0.8	400	2468	1880	-16.1	3.8	1.1	-9.3	-2.2	-0.6
450	2262	1580	-24.7	5.2	1.5	-14.3	-3.0	-0.9	450	2384	1754	-23.4	5.0	1.4	-12.0	-2.5	-0.7
500	2169	1452	-34.3	6.6	1.9	-18.0	-3.4	-1.0	500	2301	1634	-32.3	6.2	1.8	-15.0	-2.9	-0.8
550	2077	1332	-45.6	7.9	2.3	-22.2	-3.9	-1.1	550	2220	1521	-42.8	7.4	2.2	-18.5	-3.2	-0.9
600	1988	1220	-59.0	9.4	2.7	-27.0	-4.3	-1.3	600	2140	1414	-55.1	8.8	2.6	-22.4	-3.6	-1.0
650	1902	1116	-74.6	11.0	3.2	-32.3	-4.7	-1.4	650	2062	1313	-69.3	10.2	3.0	-26.7	-3.9	-1.1
700	1817	1020	-92.6	12.6	3.7	-38.3	-5.2	-1.5	700	1986	1218	-85.5	11.7	3.4	-31.5	-4.3	-1.3

Barnes VOR-TX LR Ammunition

7mm PRC 160gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.608			G7 BC: 0.305						G1 BC: 0.608			G7 BC: 0.305					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3050	3306	----	----	----	----	----	----	0	3050	3306	----	----	----	----	----	----
50	2970	3134	0.4	-0.8	-0.2	-0.1	-0.2	-0.1	50	2981	3158	0.4	-0.8	-0.2	-0.1	-0.2	-0.1
100	2891	2970	1.3	-1.3	-0.4	-0.5	-0.4	-0.1	100	2913	3015	1.3	-1.2	-0.4	-0.4	-0.4	-0.1
150	2814	2814	1.2	-0.8	-0.2	-1.1	-0.7	-0.2	150	2846	2879	1.2	-0.8	-0.2	-0.9	-0.6	-0.2
200	2738	2664	0.0	0.0	0.0	-1.9	-0.9	-0.3	200	2780	2747	0.0	0.0	0.0	-1.7	-0.8	-0.2
250	2663	2520	-2.4	0.9	0.3	-3.1	-1.2	-0.3	250	2715	2620	-2.3	0.9	0.3	-2.6	-1.0	-0.3
300	2590	2383	-6.0	1.9	0.6	-4.4	-1.4	-0.4	300	2651	2498	-5.8	1.8	0.5	-3.8	-1.2	-0.4
350	2517	2252	-10.9	3.0	0.9	-6.1	-1.7	-0.5	350	2589	2381	-10.5	2.9	0.8	-5.2	-1.4	-0.4
400	2446	2127	-17.1	4.1	1.2	-8.1	-1.9	-0.6	400	2526	2268	-16.5	3.9	1.1	-6.9	-1.6	-0.5
450	2376	2007	-24.8	5.3	1.5	-10.4	-2.2	-0.6	450	2465	2160	-23.9	5.1	1.5	-8.8	-1.9	-0.5
500	2308	1892	-34.1	6.5	1.9	-13.0	-2.5	-0.7	500	2405	2055	-23.7	4.5	1.3	-11.0	-2.1	-0.6
550	2240	1783	-45.0	7.8	2.3	-16.0	-2.8	-0.8	550	2345	1955	-43.1	7.5	2.2	-13.4	-2.3	-0.7
600	2173	1678	-57.6	9.2	2.7	-19.3	-3.1	-0.9	600	2287	1858	-55.0	8.7	2.5	-16.2	-2.6	-0.8
650	2108	1579	-72.1	10.6	3.1	-23.0	-3.4	-1.0	650	2229	1765	-68.5	10.1	2.9	-19.2	-2.8	-0.8
700	2043	1484	-88.5	12.1	3.5	-27.0	-3.7	-1.1	700	2172	1676	-83.8	11.4	3.3	-22.6	-3.1	-0.9

Barnes VOR-TX LR Ammunition

7mm Remington Ultra Magnum 145gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.449			G7 BC: 0.221						G1 BC: 0.449			G7 BC: 0.221					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3350	3613	----	----	----	----	----	----	0	3350	3613	----	----	----	----	----	----
50	3234	3368	0.2	-0.4	-0.1	-0.1	-0.2	-0.1	50	3250	3401	0.2	-0.4	-0.1	-0.1	-0.2	-0.1
100	3121	3137	1.0	-1.0	-0.3	-0.6	-0.6	-0.2	100	3152	3199	1.0	-1.0	-0.3	-0.5	-0.5	-0.1
150	3011	2920	1.0	-0.6	-0.2	-1.3	-0.8	-0.2	150	3056	3008	1.0	-0.6	-0.2	-1.1	-0.7	-0.2
200	2904	2715	0.0	0.0	0.0	-2.4	-1.1	-0.3	200	2963	2827	0.0	0.0	0.0	-2.0	-1.0	-0.3
250	2799	2523	-2.0	0.8	0.2	-3.7	-1.4	-0.4	250	2871	2655	-2.0	0.8	0.2	-3.2	-1.2	-0.4
300	2697	2342	-5.2	1.7	0.5	-5.5	-1.8	-0.5	300	2782	2493	-5.0	1.6	0.5	-4.6	-1.5	-0.4
350	2597	2172	-9.5	2.6	0.8	-7.5	-2.0	-0.6	350	2694	2338	-9.1	2.5	0.7	-6.4	-1.7	-0.5
400	2499	2011	-15.1	3.6	1.0	-10.0	-2.4	-0.7	400	2609	2191	-14.4	3.4	1.0	-8.5	-2.0	-0.6
450	2404	1861	-22.1	4.7	1.4	-12.9	-2.7	-0.8	450	2524	2052	-21.0	4.5	1.3	-10.9	-2.3	-0.7
500	2310	1719	-30.7	5.9	1.7	-16.3	-3.1	-0.9	500	2442	1920	-29.0	5.5	1.6	-13.6	-2.6	-0.8
550	2219	1585	-40.8	7.1	2.1	-20.0	-3.5	-1.0	550	2361	1795	-38.4	6.7	1.9	-16.8	-2.9	-0.8
600	2129	1460	-52.7	8.4	2.4	-24.3	-3.9	-1.1	600	2281	1676	-49.4	7.9	2.3	-20.3	-3.2	-0.9
650	2042	1342	-66.6	9.8	2.8	-29.1	-4.3	-1.2	650	2203	1563	-62.1	9.1	2.7	-24.2	-3.6	-1.0
700	1956	1233	-82.5	11.3	3.3	-34.4	-4.7	-1.4	700	2126	1456	-76.5	10.4	3.0	-28.5	-3.9	-1.1

Barnes VOR-TX LR Ammunition

30-06 Springfield 175gr VOR-TX LR																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.508			G7 BC: 0.254						G1 BC: 0.508			G7 BC: 0.254					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	2800	3047	----	----	----	----	----	----	0	2800	3047	----	----	----	----	----	----
50	2710	2853	0.7	-1.4	-0.4	0.2	0.3	0.1	50	2722	2880	0.7	-1.3	-0.4	0.1	0.2	0.1
100	2621	2670	1.8	-1.7	-0.5	0.6	0.6	0.2	100	2645	2720	1.7	-1.7	-0.5	0.5	0.5	0.2
150	2534	2496	1.6	-1.0	-0.3	1.5	0.9	0.3	150	2570	2567	1.5	-1.0	-0.3	1.2	0.8	0.2
200	2449	2330	0.0	0.0	0.0	2.6	1.3	0.4	200	2496	2422	0.0	0.0	0.0	2.2	1.1	0.3
250	2365	2174	-3.0	1.2	0.3	4.2	1.6	0.5	250	2423	2283	-2.9	1.1	0.3	3.5	1.4	0.4
300	2283	2026	-7.6	2.4	0.7	6.1	1.9	0.6	300	2352	2150	-7.3	2.3	0.7	5.2	1.6	0.5
350	2202	1885	-13.8	3.8	1.1	8.4	2.3	0.7	350	2281	2023	-13.3	3.6	1.1	7.1	1.9	0.6
400	2124	1753	-21.9	5.2	1.5	11.2	2.7	0.8	400	2212	1902	-20.9	5.0	1.5	9.5	2.3	0.7
450	2046	1628	-31.8	6.8	2.0	14.5	3.1	0.9	450	2144	1787	-30.4	6.4	1.9	12.2	2.6	0.8
500	1971	1510	-43.9	8.4	2.4	18.2	3.5	1.0	500	2077	1677	-41.7	8.0	2.3	15.2	2.9	0.8
550	1897	1399	-58.1	10.1	2.9	22.4	3.9	1.1	550	2012	1573	-55.0	9.5	2.8	18.7	3.3	0.9
600	1825	1295	-74.8	11.9	3.5	27.2	4.3	1.3	600	1947	1474	-70.5	11.2	3.3	22.6	3.6	1.0
650	1755	1197	-94.1	13.8	4.0	32.5	4.8	1.4	650	1884	1380	-88.2	13.0	3.8	27.0	4.0	1.2
700	1687	1106	-116.2	15.9	4.6	38.4	5.2	1.5	700	1822	1291	-108.4	14.8	4.3	31.8	4.3	1.3

Barnes VOR-TX LR Ammunition

300 Win Mag 190gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.499			G7 BC: 0.259						G1 BC: 0.499			G7 BC: 0.259					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	2880	3500	----	----	----	----	----	----	0	2880	3500	----	----	----	----	----	----
50	2786	3276	0.6	-1.2	-0.4	0.2	0.3	0.1	50	2799	3307	0.6	-1.2	-0.3	0.1	0.2	0.1
100	2694	3064	1.7	-1.6	-0.5	0.6	0.6	0.2	100	2720	3122	1.6	-1.5	-0.4	0.5	0.5	0.1
150	2604	2862	1.5	-0.9	-0.3	1.4	0.9	0.3	150	2642	2946	1.4	-0.9	-0.3	1.2	0.8	0.2
200	2516	2672	0.0	0.0	0.0	2.6	1.2	0.4	200	2566	2778	0.0	0.0	0.0	2.2	1.0	0.3
250	2430	2491	-2.8	1.1	0.3	4.1	1.6	0.5	250	2491	2618	-2.7	1.0	0.3	3.5	1.3	0.4
300	2345	2321	-7.2	2.3	0.7	6.0	1.9	0.6	300	2417	2465	-6.9	2.2	0.6	5.1	1.6	0.5
350	2262	2159	-13.0	3.6	1.0	8.3	2.3	0.7	350	2344	2319	-12.5	3.4	1.0	7.0	1.9	0.6
400	2180	2006	-20.6	4.9	1.4	11.0	2.6	0.8	400	2273	2180	-19.7	4.7	1.4	9.3	2.2	0.6
450	2101	1862	-30.0	6.4	1.9	14.2	3.0	0.9	450	2203	2047	-28.6	6.1	1.8	11.9	2.5	0.7
500	2022	1726	-41.4	7.9	2.3	17.8	3.4	1.0	500	2134	1921	-39.3	7.5	2.2	14.9	2.8	0.8
550	1946	1598	-54.9	9.5	2.8	21.9	3.8	1.1	550	2066	1801	-51.9	9.0	2.6	18.3	3.2	0.9
600	1872	1478	-70.7	11.3	3.3	26.6	4.2	1.2	600	1999	1687	-66.5	10.6	3.1	22.1	3.5	1.0
650	1799	1366	-89.0	13.1	3.8	31.8	4.7	1.4	650	1934	1579	-83.4	12.2	3.6	26.4	3.9	1.1
700	1728	1261	-110.0	15.0	4.4	37.6	5.1	1.5	700	1870	1476	-102.5	14.0	4.1	31.1	4.2	1.2

Barnes VOR-TX LR Ammunition

300 PRC 208gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.633			G7 BC: 0.316						G1 BC: 0.633			G7 BC: 0.316					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	2860	3779	----	----	----	----	----	----	0	2860	3779	----	----	----	----	----	----
50	2786	3586	0.6	-1.2	-0.3	-0.1	-0.2	-0.1	50	2797	3614	0.6	-1.1	-0.3	-0.1	-0.2	-0.1
100	2714	3402	1.6	-1.5	-0.4	-0.4	-0.4	-0.1	100	2735	3456	1.6	-1.5	-0.4	-0.4	-0.4	-0.1
150	2642	3225	1.4	-0.9	-0.3	-1.0	-0.6	-0.2	150	2674	3303	1.4	-0.9	-0.3	-1.0	-0.6	-0.2
200	2572	3056	0.0	0.0	0.0	-1.8	-0.9	-0.3	200	2614	3156	0.0	0.0	0.0	-1.7	-0.8	-0.2
250	2503	2894	-2.7	1.0	0.3	-2.9	-1.1	-0.3	250	2554	3014	-2.7	1.0	0.3	-2.7	-1.0	-0.3
300	2435	2739	-6.9	2.2	0.6	-4.2	-1.3	-0.4	300	2495	2877	-6.7	2.1	0.6	-3.9	-1.2	-0.4
350	2368	2590	-12.5	3.4	1.0	-5.8	-1.6	-0.5	350	2438	2745	-12.1	3.3	1.0	-5.4	-1.5	-0.4
400	2302	2448	-19.6	4.7	1.4	-7.7	-1.8	-0.5	400	2380	2618	-18.9	4.5	1.3	-7.1	-1.7	-0.5
450	2237	2311	-28.4	6.0	1.8	-9.8	-2.1	-0.6	450	2324	2495	-27.3	5.8	1.7	-9.1	-1.9	-0.6
500	2173	2181	-38.9	7.4	2.2	-12.3	-2.3	-0.7	500	2268	2377	-37.3	7.1	2.1	-11.4	-2.2	-0.6
550	2110	2057	-51.3	8.9	2.6	-15.1	-2.6	-0.8	550	2213	2263	-49.0	8.5	2.5	-13.9	-2.4	-0.7
600	2048	1938	-65.6	10.4	3.0	-18.2	-2.9	-0.8	600	2159	2154	-62.5	9.9	2.9	-16.8	-2.7	-0.8
650	1987	1824	-82.0	12.0	3.5	-21.7	-3.2	-0.9	650	2106	2049	-77.8	11.4	3.3	-19.9	-2.9	-0.9
700	1928	1716	-100.6	13.7	4.0	-25.5	-3.5	-1.0	700	2053	1948	-95.1	13.0	3.8	-23.4	-3.2	-0.9

Barnes VOR-TX LR Ammunition

300 Remington Ultra Magnum 190gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 øF			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 øF			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.540			G7 BC: 0.266						G1 BC: 0.540			G7 BC: 0.266					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	3125	4121	----	----	----	----	----	----	0	3125	4121	----	----	----	----	----	----
50	3033	3883	0.4	-0.7	-0.2	0.1	0.2	0.1	50	3046	3915	0.3	-0.6	-0.2	0.1	0.2	0.1
100	2943	3656	1.3	-1.2	-0.4	0.5	0.5	0.1	100	2968	3718	1.2	-1.2	-0.3	0.4	0.4	0.1
150	2855	3441	1.2	-0.7	-0.2	1.2	0.7	0.2	150	2892	3530	1.1	-0.7	-0.2	1.0	0.6	0.2
200	2769	3236	0.0	0.0	0.0	2.1	1.0	0.3	200	2817	3349	0.0	0.0	0.0	1.8	0.9	0.3
250	2685	3041	-2.3	0.9	0.3	3.4	1.3	0.4	250	2744	3176	-2.2	0.9	0.2	2.9	1.1	0.3
300	2602	2856	-5.8	1.8	0.5	4.9	1.6	0.5	300	2671	3011	-5.6	1.8	0.5	4.2	1.3	0.4
350	2520	2680	-10.6	2.9	0.8	6.8	1.8	0.5	350	2600	2853	-10.2	2.8	0.8	5.7	1.6	0.5
400	2440	2513	-16.7	4.0	1.2	9.0	2.1	0.6	400	2530	2701	-16.1	3.8	1.1	7.6	1.8	0.5
450	2361	2353	-24.4	5.2	1.5	11.5	2.4	0.7	450	2461	2556	-23.3	5.0	1.4	9.7	2.1	0.6
500	2284	2202	-33.5	6.4	1.9	14.4	2.8	0.8	500	2393	2417	-32.0	6.1	1.8	12.1	2.3	0.7
550	2209	2058	-44.4	7.7	2.2	17.7	3.1	0.9	550	2327	2284	-42.2	7.3	2.1	14.9	2.6	0.8
600	2134	1922	-57.0	9.1	2.6	21.4	3.4	1.0	600	2261	2157	-54.0	8.6	2.5	17.9	2.9	0.8
650	2061	1793	-71.5	10.5	3.1	25.6	3.8	1.1	650	2196	2035	-67.5	9.9	2.9	21.3	3.1	0.9
700	1990	1671	-88.1	12.0	3.5	30.2	4.1	1.2	700	2133	1919	-82.8	11.3	3.3	25.1	3.4	1.0

Barnes VOR-TX LR Ammunition

338 Remington Ultra Magnum 250gr LRX BT																	
Altitude: 0 feet			Zero Range: 200 yards			Wind Speed: 10 mph			Altitude: 5000 feet			Zero Range: 200 yards			Wind Speed: 10 mph		
Temp: 59 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk			Temp: 40 °F			Sight Height: 1.5 in			Wind Dir: 03:00 O'clk		
G1 BC: 0.602			G7 BC: 0.294						G1 BC: 0.602			G7 BC: 0.294					
Range	Velocity	Energy	Drop	Zero Adj.		Drift			Range	Velocity	Energy	Drop	Zero Adj.		Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL
0	2910	4702	----	----	----	----	----	----	0	2910	4702	----	----	----	----	----	----
50	2832	4452	0.6	-1.1	-0.3	0.1	0.2	0.1	50	2843	4486	0.5	-1.0	-0.3	0.1	0.2	0.1
100	2755	4213	1.5	-1.5	-0.4	-0.5	-0.5	-0.1	100	2776	4279	1.5	-1.4	-0.4	0.4	0.4	0.1
150	2679	3985	1.4	-0.9	-0.3	1.2	0.7	0.2	150	2711	4080	1.3	-0.9	-0.2	1.0	0.6	0.2
200	2604	3766	0.0	0.0	0.0	2.1	1.0	0.3	200	2646	3888	0.0	0.0	0.0	1.8	0.8	0.2
250	2531	3558	-2.7	1.0	0.3	3.3	1.3	0.4	250	2583	3704	-2.6	1.0	0.3	2.8	1.1	0.3
300	2459	3358	-6.7	2.1	0.6	4.8	1.5	0.4	300	2520	3526	-6.5	2.1	0.6	4.1	1.3	0.4
350	2388	3167	-12.1	3.3	1.0	6.6	1.8	0.5	350	2458	3356	-11.7	3.2	0.9	5.6	1.5	0.4
400	2319	2985	-19.1	4.6	1.3	8.8	2.1	0.6	400	2397	3192	-18.4	4.4	1.3	7.4	1.8	0.5
450	2250	2811	-27.7	5.9	1.7	11.3	2.4	0.7	450	2337	3034	-26.6	5.7	1.6	9.5	2.0	0.6
500	2183	2645	-38.0	7.3	2.1	14.1	2.7	0.8	500	2278	2882	-36.4	7.0	2.0	11.9	2.3	0.7
550	2116	2487	-50.1	8.7	2.5	17.3	3.0	0.9	550	2220	2737	-47.9	8.3	2.4	14.5	2.5	0.7
600	2051	2336	-64.2	10.2	3.0	20.9	3.3	1.0	600	2163	2597	-61.1	9.7	2.8	17.5	2.8	0.8
650	1987	2193	-80.3	11.8	3.4	24.9	3.7	1.1	650	2106	2462	-76.2	11.2	3.3	20.8	3.1	0.9
700	1924	2056	-98.7	13.5	3.9	29.3	4.0	1.2	700	2050	2334	-93.3	12.7	3.7	24.4	3.3	1.0

Barnes VOR-TX LR Ammunition

375 Remington Ultra Magnum 270gr LRX BT																			
Altitude: 0 feet Zero Range: 200 yards Wind Speed: 10 mph									Altitude: 5000 feet Zero Range: 200 yards Wind Speed: 10 mph										
Temp: 59 °F Sight Height: 1.5 in Wind Dir: 03:00 O'clk									Temp: 40 °F Sight Height: 1.5 in Wind Dir: 03:00 O'clk										
G1 BC: 0.449 G7 BC: 0.224									G1 BC: 0.449 G7 BC: 0.224										
Range	Velocity	Energy	Drop	Zero Adj.			Drift			Range	Velocity	Energy	Drop	Zero Adj.			Drift		
Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL	Yards	f/s	ft-lb	inches	MOA	MIL	inches	MOA	MIL		
0	2980	5325	----	----	----	----	----	----	0	2980	5325	----	----	----	----	----	----		
50	2874	4952	0.5	-1.0	-0.3	0.2	0.3	0.1	50	2888	5003	0.5	-1.0	-0.3	0.1	0.3	0.1		
100	2770	4600	1.5	-1.5	-0.4	0.7	0.6	0.2	100	2798	4696	1.5	-1.4	-0.4	0.6	0.5	0.2		
150	2668	4269	1.4	-0.9	-0.3	1.5	1.0	0.3	150	2710	4406	1.3	-0.8	-0.2	1.3	0.8	0.2		
200	2569	3957	0.0	0.0	0.0	2.7	1.3	0.4	200	2624	4130	0.0	0.0	0.0	2.3	1.1	0.3		
250	2472	3663	-2.7	1.0	0.3	4.3	1.7	0.5	250	2540	3868	-2.6	1.0	0.3	3.7	1.4	0.4		
300	2377	3387	-6.8	2.2	0.6	6.4	2.0	0.6	300	2457	3620	-6.5	2.1	0.6	5.4	1.7	0.5		
350	2284	3127	-12.5	3.4	1.0	8.9	2.4	0.7	350	2375	3384	-11.9	3.2	0.9	7.5	2.0	0.6		
400	2193	2883	-19.8	4.7	1.4	11.8	2.8	0.8	400	2296	3160	-18.8	4.5	1.3	9.9	2.4	0.7		
450	2104	2654	-28.9	6.1	1.8	15.2	3.2	0.9	450	2217	2948	-27.4	5.8	1.7	12.8	2.7	0.8		
500	2017	2440	-40.0	7.6	2.2	19.2	3.7	1.1	500	2140	2747	-37.7	7.2	2.1	16.0	3.1	0.9		